3/8" & 1/2" CLOSE QUARTER DRILLS

0375-6
DOUBLE INSULATED
3/8" CLOSE QUARTER DRILL
0-1300 RPM

0379-1
DOUBLE INSULATED
1/2" CLOSE QUARTER DRILL
0-750 RPM

UNIQUE 55° ANGLED CHUCK FOR CLOSE QUARTER DRILLING

All Ball and Roller Bearings • Helical Cut, Heat Treated Gears for Heavy-Duty Industrial/Construction Applications

- **Unique Design – 55° Angled Chuck** For easy access to tight places
- **Lightweight**
- **Comfortable Grip, Efficient Paddle Switch**
- **High Impact Housing**
- **Quiet Running**



SPECIFICATIONS

CATALOG NUMBER	CAPACITY IN STEEL	VOLTS AC ONLY	AMPS	NO LOAD RPM	GEAR TRAIN	SPINDLE DIAMETER AND THREAD	REPLACEMENT CHUCK CATALOG NO. CHUCK KEY INCLUDED	REPLACEMENT CHUCK KEY CATALOG NO.	LENGTH (IN.)	NET WGT. LBS.	SHIP. WGT. LBS.
0375-6	3/8"	120	3.5	0-1300	DOUBLE	3/8" - 24	48-66-2115	48-66-3240	10	3.0	4.5
0379-1	1/2"	120	3.5	0-750	DOUBLE	3/8" - 24	48-66-2120	48-66-3480	10	3.0	4.5

STANDARD EQUIPMENT: FOR 0375-6 AND 0379-1 – Chuck Key and Rubber Flex Key Holder.

IMPACT WRENCH

9066-6
DOUBLE INSULATED
1/2" SQUARE DRIVE

9068 (KIT)
DOUBLE INSULATED
INCLUDES 9066-6 IMPACT WRENCH, SOCKETS: 1/2", 9/16", 5/8", 11/16", 3/4", 13/16" AND STEEL CARRYING CASE

1/2" SQUARE DRIVE WITH BALL DETENT
2800 IMPACTS PER MINUTE
240 FT.-LBS. TORQUE

Powerful 6.8 AMP MILWAUKEE Motor • Balanced, Compact, Lightweight

9066-6 AND 9068 IMPACT WRENCH FEATURES

- **Heavy-Duty Rocker Switch**
- **Glass Reinforced Nylon Handle And Motor Housing** Strong, lightweight. Textured nylon handle helps keep grip cool.
- **Heavy-Duty Aluminum Gear Case**
- **Easy Access To Brushes**

SPECIFICATIONS

CAT. NO.	VOLTS AC-DC	AMPS	IMPACTS PER MINUTE	NO LOAD RPM	TORQUE FT./LBS.	LENGTH INCHES	NET WGT. LBS.	SHIP WGT. LBS.
9066-6	120	6.8	2800	2400	240	9-15/16	6	7
9068 KIT	120	6.8	2800	2400	240	9-15/16	13	13-3/4

STANDARD EQUIPMENT FOR 9068 – No. 9066-6 Impact Wrench, Steel Carrying Case, and the Following Sizes of Hex Sockets with 1/2" Square Drive: 1/2", 9/16", 5/8" 11/16", 3/4", 13/16".

ACCESSORIES

HEX SOCKETS WITH 1/2" SQUARE DRIVE
Standard equipment for 9068 Kit.

49-66-3080	1/2"	**49-66-3110**	11/16"
49-66-3090	9/16"	**49-66-3120**	3/4"
49-66-3100	5/8"	**49-66-3130**	13/16"

STEEL CARRYING CASE
48-55-5050 (Standard equipment for 9068 Kit.)



EXTENSION BAR
48-95-5000 Adapts to 1/2" Square Drive. Provides 5" additional length where required for use with sockets.

POSITIVE DETENT KIT
49-17-0405 Replaces standard round detent pin on square drive. Socket will not slip off unless detent pin is pressed in. **Below Serial No. 656-38701, Use 49-17-0400 Positive Detent Kit**

UNIVERSAL JOINT

48-03-0500 Fits 1/2" Square Drive and used with Hex Sockets to reach difficult places at various angles...also allows clearance around obstructions.

TOOL HANGER
49-17-0230 For Impact Wrench model 9066-6.



PROTECTIVE BUMPER RINGS
48-50-1000 For Impact Wrench model 9066-6.

TYPE "E" GREASE
49-08-4122 1 lb. can.

TYPE "N" GREASE
49-08-4230 6 ounce tube.